



850 Transmitter

Nominal Output Power:	0.6W and 2W Output
Frequency:	9.82 kHz + .002% Crystal Controlled for interference resistance
Battery Type:	Rechargeable Lead-Acid 6V Charging is by 115V, 60Hz AC Power source (by request), or optional 12V vehicle mount charger
Battery Life:	92 hours Continuous Use
Impedance Matching	Automatic, no adjustments
Dimensions:	8"L x 4.125"W x 6.75"H (20.3 x 10.5 x 17.2 cm)
Weight:	5.8 lbs (2.6 kg)

850 Receiver

Trace Accuracy:	+1 inch from 0-3 ft (91 cm) +3% over 3 ft (91 cm) in depth
Depth Readout Accuracy:	± (5% + 2") under normal conditions
Depth Readout Range:	To 13 ft (400 cm)
Sensitivity Control:	Automatic, no adjustments
Battery Type:	4 NEDA 1604A Alkaline (9V)
Battery Test:	Indicated on Meter
Battery Life:	150 hours
Temperature Range:	0 - 110°F (-18 - 43°C)
Dimensions:	(Extended Length) 32.5"L x 7.5"W x 12.5"H (82.6 x 19.1 x 31.8 cm)
Weight:	4.4 lbs (2.0 kg)

FEATURES

- Excellent Isolation From Adjacent Utilities
- Efficient High Power 2 Watt Transmitter Facilitates Long Distance Locating
- Transmitter Impedance Matching Maximizes Battery Life
- Saves You Time – Simultaneous Peak/Null
- Shows You The Path – Left/Right Guidance System and Audible Tone Pinpoints Your Utility and Indicates Strength of Transmitted Signal – Digital Signal Strength
- No manual Gain Adjustments – Fully Automated
- Determines Depth – Quick and Easy Push Button Depth Lightweight, and All Readouts are Line-Of-Sight, Reducing User Fatigue

STANDARD EQUIPMENT

Transmitter, Receiver, Conductor Attachments, Ground Rod, Carrying Case, and Operation Manual.

ACCESSORIES

Metroclamps 4290 (2"), 5120 (4"), 4890 (8")
Headphones (P/N 183045), Sondes (P/N SON982, P/N SONH9.8K), Training Videos (P/N 600A073)



SERVICE CENTER, SALES AND TECHNICAL SUPPORT INFORMATION

Corporate Headquarters
3251 Olcott Street
Santa Clara, CA 95054
800-446-3392
408-734-1400 Direct
408-734-1415 Fax
www.metrotech.com
sales@metrotech.com

Metrotech Eastern U.S. Service Center
5211 Linbar Drive, Suite 503
Nashville, TN 37211
800-624-6210
615-366-7323 Direct
615-360-9855 Fax
nashville@metrotech.com

Metrotech European Service Center
Seba KMT
Dr. Herbert Iann St. 6
96148 Baunach, Germany
+49 9 544 680
+49 9 544 2273 Fax
service@sebakmt.com